



de Heus- XCMG
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XE270EV

Standard features include:

- Fully electric drive – zero emissions and whisper quiet
- Powerful electric motor with a capacity of 140 kW
- Lithium iron phosphate (LFP) battery pack of 525 kWh
 - Nominal voltage: 600 V
 - Operating time up to 8 hours, depending on use
 - Fast charging in approx. 1.5 to 2 hours via DC charger
- Double variable piston pump in the hydraulic system
- Maximum system pressure of 34.3 MPa for powerful hydraulic performance
- ROPS/FOPS certified cabin with:
 - Luxury suspension comfort seat
 - Air conditioning and heating
 - Large colour display with battery status and machine information
 - Standard rear-view and side cameras
- Automatic energy management system for efficient battery use
- Regenerative braking system for energy recovery during use
- All-round LED work lights for optimal visibility
- Central lubrication points for easy maintenance
- Suitable for various attachments thanks to powerful hydraulic system
- Standard bucket capacity of 1.2–1.6 m³ (depending on configuration)



€0.00

Specifications

DIMENSIONS

Cabin width	2980
Counterweight free space	1110
Cradle base	3837
Ground clearance	490
Height of tracks	940
Height to top of roof	3150
Max. Digging depth	6925
Max. Digging height	10095
Max. Tipping height	7170
Max. Vertical digging depth	5520
Max. excavation radius	10240
Min. forcing radius	3645
Overall length with bin	10825
Overall width	3190
Platform width	2980
Track width	2590
Width of tracks	900

ELECTRIC MOTOR

Battery capacity	525
Driving motor	140

ENGINE

Cooling	Liquid
---------	--------

HYDRAULIC SYSTEM

Driving system pressure	343
Main pressure safety valve	343
Main pump output	238
Steering pressure	39
Swing system pressure	280

OTHER

Hydro tank	220
------------	-----

**OTHER
TECHNICAL SPECIFICATIONS**

Arm digging force	129
Ground pressure	52
Max. Digging force	185
Rotation speed	11

WEIGHT

Own weight	27450
------------	-------

Pictures







